



The easy to use touch screen on the control panel of the AR-M350/450 N Digital IMAGER quickly guides users step-by-step through various functions.

Specifications

General

Type:	Console
Copy system:	Dry, electrostatic transfer system
Paper size:	Max. 11" x 17" / Min. 5.5" x 8.5"
Paper capacity:	500 sheets, expandable up to 3,100 sheets with options
Copy/print speed (max):	35/45 cpm/ppm (8.5" x 11")
Memory:	64MB, upgradable to 320MB with options, 5GB HDD
Warm-up time ¹ :	Less than 80 seconds
First copy time:	4.6 seconds (8.5" x 11", 1st paper tray, fast platen mode)
Power requirements:	Rated local AC voltage \pm 10%, 50/60 Hz
Power consumption:	Max. 1.6 kW
Dimensions (WxDxH) ² :	32 17/32" x 26 31/32" x 43 15/16"
Weight ³ :	215 lbs

Printer

Resolution:	600 dpi, 1,200 dpi equivalent with smoothing technology
Interface:	IEEE 1284 parallel port
Printer drivers:	Windows [®] 95/98/Me, Windows NT [®] 4.0, Windows [®] 2000, Macintosh System 8.5.1-9.x
PDL (emulsion):	PCL5e, PCL6, PostScript Level 3 (option)
Available fonts:	45 fonts for HP PCL, 136 fonts for PS (with optional AR-PK1)
Other features:	Paper/output tray selection, duplex print, watermarks, pamphlet style, staple (3 patterns), job retention for confidential/sample print, N-up, B&W reverse, mirror image, form overlay, fit to page, auto configuration, easy print (stores settings), confidential print, sample print. Note: some features are not available according to the printer driver used.

Network Interface Card (Standard AR-NC5J)

Hardware interface:	10Base-T, 100Base-TX
Support platforms:	UNIX, Windows 95/98/Me, Windows NT 4.0, Windows 2000, Novell Netware 3.x/4.x (IntranetWare)/Netware5, Macintosh System 8.5.1-9.x
Network protocols:	IPX/SPX for Novell environments, TCP/IP for Windows and UNIX environments, EtherTalk for Macintosh environments
Printing protocols:	Novell Printserver Application w/ NCS and Bindery, Printer resident LPD (includes reaction to LPQ request), TCP FTP for downloading of print files, EtherTalk printing, IPP, NetRF II for Windows

Copier

Original size:	Max. 11" x 17"
Continuous copy:	Max. 999 copies
Resolution copy:	600 dpi
Zoom range:	From 25 to 400% with 8 preset ratios (4 reduction + 4 enlargement). From 25 to 200% when equipped with DSPF
Other features:	Auto paper selection, auto magnification selection, paper type selection (by type setting), auto tray switching, E-Sort, rotation copy, reserved copy, pre-heat/auto power shut-off modes, copy auditing (100 accounts), margin shift, edge/centre erase, dual page copy mode, multi-shot copy (N in 1), booklet copy

Optional Scanner Expansion Kit

Resolution:	200, 300, 600 dpi
Compatibility:	TWAIN compliant (push out method)
Sharpdesk licenses:	10-user licenses included
Optional Fax	
Transmission time ¹ :	2 seconds (Super G3); 6 seconds (G3)
Compression method:	MH, MR, MMR, JBIG
Modem speed:	33.6Kbps/2.4Kbps automatic fallback
Intercommunication:	Super G3, G3
Communication line:	PSTN, PBX
# of support lines:	1
Image quality:	256 grayscale levels
Exposure adjustment:	Dark/Auto/Light
Resolution settings:	Normal/Small Letter/Fine/Extra Fine
One touch dial keys:	500 (e-mail addresses included)

Design and specifications are subject to change without notice.

Sharp is a registered trademark of Sharp Corporation. All other trademarks and registered trademarks are property of their respective holders.
¹With ITU-T No.1 chart standard resolution, SUPER G3 mode, 33,600 bps, JBIG compression.
²At rated voltage, 20°C (68°F), 65% RH.
³Dimensions and weight include scanner rack and stand.